

SKI BINDING AND SNOWBOARD BINDING

BACKGROUND OF THE INVENTION

Field of the Invention

5 This invention relates to a ski binding or a snowboard binding having boot holder components on the front end or the toe end and on the rear end or the heel end, being arranged on a rail guide on the ski end or on the snowboard end, extending in the longitudinal direction of the ski or
10 snowboard.

Description of the Prior Art

A corresponding ski binding is known from German Utility Model 91 17 298 U1. According to this publication, separate
15 guide rail plates are arranged on the ski for the boot holder component on the toe end and on the heel end, with the above-mentioned components being guided displaceably in these guide rail plates in the longitudinal direction of the ski. The boot holder components are connected by means
20 of toothed rods to a pinion which is accommodated in a housing arranged between the two guide rail plates and which engages with the two toothed rods in such a way that the boot holder components are moved toward or away from one another, depending on the direction of rotation, as the
25 pinion is rotated. The set positions of the boot holder components are locked by means of a lock for the pinion or a locking device by means of which at least one boot holder component can be locked on the respective guide rail plate.

30 The gearbox having the pinion is arranged so that it is movable vertically such that the toothed rods can be lifted up from the top side of the ski in the area of the pinion in the case of flexing movements of the ski.

35 International Patent WO 95/05219 discloses a snowboard whose supporting structure has two countersunk guide rail pairs integrated into it. Two sliding blocks, each of which

108101 " 232350

has a borehole with an internal screw thread to receive fastening screws of snowboard bindings, are guided displaceably but unrotatably in each guide rail. When the fastening screws are screwed into the threaded boreholes
5 with a significant torque, the sliding blocks and thus the snowboard bindings are fixedly secured on the snowboard or in the guide rails. The guide rails offer the possibility of practically infinitely variable positioning of the bindings on the snowboard.

10

As a rule, however, bindings on skis and snowboards are secured directly with fastening screws that have previously been screwed into boreholes provided in predetermined positions on the ski or snowboard.

15

SUMMARY OF THE INVENTION

The object of this invention is to permit rigging of ski bindings and snowboard bindings mostly without the use of tools and to permit the lowest possible burden on the ski
20 or snowboard due to the binding.

This object is achieved according to this invention by a ski binding or a snowboard binding having boot holder components on the front end or the toe end and on the rear
25 end or the heel end, said boot holder components being displaceably secured vertically in a fixed manner on the ski with a form-fitting connection on a rail guide which extends in the longitudinal direction of the ski on the side of the ski or the snowboard, said rail guide being
30 integrated into the ski or snowboard and being connected or connectable by means of connection elements in the longitudinal direction of the rail guide on a holder that is or can be secured in a fixed manner on the ski or snowboard between the boot holder components.

35

This invention is based on the general idea of inserting boot holder components into guide rails which are present

09982757 101301

5

10

20

DESCRIPTION OF THE PREFERRED EMBODIMENTS

25

30

35

This implements the general idea of providing a continuously effective restricted guidance for locking the
15 respective positions set for the boot holder components
such that it cannot be eliminated inadvertently or on
purpose.

In an especially expedient embodiment, the connection elements are formed by a threaded spindle which is in an axially fixed rotational mount on the holding device and is screwed with a right-handed threaded section into an element with an internal screw thread of the one boot holder component, and a left-handed threaded section is screwed into a corresponding element having an internal screw thread on the other boot holder component, so that with a rotational adjustment of the threaded spindle, the boot holder components are brought either closer together or farther apart from one another. With this arrangement, the two boot holder components are displaced toward one another in opposite directions when the threaded spindle is turned.

35 Instead of this, it is also possible to provide separate threaded spindles for the two boot holder components. With this design, it is optionally also possible to provide for each threaded spindle to be mounted in an axially fixed

manner on the respective boot holder component and screwed into an internal screw thread element on the holding device to permit variation of the distance between the boot holder component and the holding device through a rotational adjustment of the respective spindle.

In all embodiments, the boot holder components may each have a base plate that is displaceable in the respective rail guide and is or can be connected to the holding device by means of the connection element. Then a front or rear boot holding device is mounted on the respective base plate, in which case one of these boot holding devices may be arranged displaceably relative to a base plate against a push-off resiliency which attempts to push this boot holding device in the direction of the other boot holding device. This push-off resiliency guarantees that the boot to be secured will be held in the boot holder components without any play; in addition, in the case of flexing movements of the ski, unwanted twisting between the boot and the boot holder components is prevented.

Brief Description of the Drawings

Moreover, with regard to preferred features of this invention, reference is made to the claims and the following explanation of the drawings, on the basis of which especially preferred embodiments of this invention are described in greater detail.

They show:

- Figure 1: a schematic side view of a detail drawing of a ski having a ski binding according to this invention,
- Figure 2: a sectional diagram according to sectional line II-II in Figure 1, and

Figure 3: a vertical longitudinal section according to sectional line III-III in Figure 2.

Detailed Description of the Preferred Embodiments

5 A ski 1, which may basically have a traditional design, has on its top side two rails 2 extending in the longitudinal direction of the ski in the central area of the ski, each rail having profiles symmetrical with the central longitudinal vertical plane of the ski in the example
10 illustrated here in Figure 2, with edge webs pointing upward and outward obliquely. A front base plate part 3, a rear base plate part 4 and a holding device housing 5 arranged between the base plate parts 3 and 4 are displaceably guided on these rails 2 in the longitudinal
15 direction of the ski, with the holding device housing 5 being undisplaceably secured by splints 6 which are inserted into corresponding, aligned recesses in the holding device housing 5 and rails 2.

20 A threaded spindle 7 is mounted radially and axially in the holding device housing 5, having a toggle-shaped handle 8 which is accessible through an upper opening in the holding device housing 5 for actuation of its rotational movement. This handle 8 can serve the function of axially
25 undisplaceable mounting of the threaded spindle 7 in interaction with transverse walls of the holding device housing 5 through which the threaded spindle passes.

Threaded spindle 7 has right-handed threaded sections 7' and left-handed threaded sections 7" projecting out of the
30 holding device housing 5 in the longitudinal direction of the ski, said threaded sections being screwed into corresponding nuts 9 and 10, which are in turn arranged in a fixed manner or at least an axially fixed manner inside
35 the base plate parts 3 and 4. With the distance between the base plate parts 3 and 4 being increased or reduced in the longitudinal direction of the skis, depending on the

09982757 101804
1008101 2528550

direction of rotation of the threaded spindle 7.

Due to the self-locking design of the threaded sections 7' and 7" of the threaded spindle 7 as well as the nuts 9 and 10 which work together with the threaded spindle, the distance set between the base plate parts 3 and 4 remains unchanged without any special securing measures. However, an additional releasable lock may also be provided. For example, the toggle-shaped handle 8 may also be secured against displacement by means of a catch lever or a lock lever, or it may be secured by the fact that a cover closing the access opening for the handle 8 in the holding device housing 5 also functions as a lock in its closed position.

To optionally be able to perform a rapid adjustment of the threaded spindle 7, a conical gearwheel 11 which is connected to the handle 8 in one piece or is integrally molded onto the handle 8 in the example of Figure 3 can be arranged in a rotationally fixed manner on the threaded spindle 7. This conical gearwheel 11 works together with another conical gearwheel 12 which can rotate about an axis perpendicular to the top side of the ski within the holding device housing 5 and has a projection 13 which is accessible from the top side of the holding device housing 5 in whose upward-turned end face a slot-shaped or out-of-round recess is provided for coupling an electrical screwdriver or the like. In this way the threaded spindle 7 can be turned comparatively rapidly by means of a motor-driven tool (a screwdriver in this case) to produce great changes in position of the base plate parts 3 and 4 accordingly.

To prevent the threaded spindle 7 from being visible or exposed to attack by dirt when the base plate parts 3 and 4 are set at a more or less great distance from the holding device housing 5, projections designed as corresponding

09982757 101301

5

10

20

30

35

form parts that can be detached from the ski 1 or are arranged on parts that can be detached from the ski 1 is also possible.

- 5 In addition, the holding device housing may also be designed entirely or partially as a part which is fixedly connected to the ski 1 or its structure or is integrated into the structure of the ski 1.

ms a77

09082757 101801